



PETRONAS TUTELA JOTA EP

EXTREME PRESSURE GREASE

Refined mineral oil and LITHIUM soap based greases with extreme pressure additives. These have good adhesiveness and resistance to water washout.

Applications

- Typical applications include earth moving equipments, construction, mining and other industrial equipments.
- Temperature range : from - 20 °C to 120 °C

Benefits

- Excellent EP properties.
- Excellent shear stability.
- Resistant to rust and corrosion.

Typical characteristics:

CHARACTERISTIC	EP00	EPO	EP 1	EP 2	EP 3	METHODS
NLGI CONSISTENCY	00	0	1	2	3	—
APPEARANCE	SMOOTH STRINGY					—
COLOUR	LIGHT BROWN					—
DROPPING POINT, min °C	160	180	180	180	180	ASTM D 566
WORKED PENETRATION, mm/10	400-430	355-385	310-340	265-295	220-250	ASTM D 217
OIL SEPARATION % max	MAX 5					ASTM D 6184
WELD LOAD IN Kgs min	250					ASTM D 2596

Customer Advice

This product data sheet and the information contained therein is believed to be accurate. Data provided is based on standard tests under laboratory conditions and is given as a guide only. No responsibility is taken by the company for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. For further assistance on product MSDS, recommendation or technical queries, please liaise with the regional technical services engineer or contact HQ technical engineers.

PETRONAS LUBRICANTS (INDIA) PVT. LTD.

204 & 205, 2nd Floor, 349 Business Point, Western Express Highway, Andheri (East), Mumbai - 400069.

Tel: (022) 6771-7500, E-mail: industrialsupport@pli.petronasindia.com